

		Spannung [V]	Schubkraft [N]	Hubgeschwindigkeit [mm/s]	Einschaltdauer [%]	Nennstrom [A]	IP Schutz	Grund-Hublänge [mm]	Hublänge max. [mm]
	Junior 1	24VDC	50 to 2000	1.3 to 55	S1/100%, S3/40%, S3/60%	0.8 to 1.2	54	100	100 to 200
	Junior 2	24VDC, 230VAC	50 to 10000	1.2 to 70	S1/100%, S3/15%, S3/40%, S3/60%	0.9 to 6	54	150	200 to 350
	Picolo 0	12VDC, 24VDC	100 to 1800	2 to 16	KB 5min		67	75	400 to 800
	Picolo XL	230AC	400 to 1200	6 to 20	KB 5min		65	100	600
	Compakt	24VDC, 400VAC	400 to 15000	1.5 to 65	S1/100%, S3/15%	1.3 to 5	54	200	1000
	Vario 1	400VAC	4000 to 50000	1 to 70	S3/15%	1.7 to 3	54	200	800
	Vario 2	400VAC	10000 to 100000	2 to 70	S3/15%	2.5 to 6	54	200	1000
	Herkules	400VAC	14000 to 50000	1 to 9	S3/15%	1.5 to 9	54	100	275

		Spannung [V]	Schubkraft [N]	Hubgeschwindigkeit [mm/s]	Einschaltdauer [%]	Nennstrom [A]	IP Schutz	Grund-Hublänge [mm]	Hublänge max. [mm]
	Econorm 0	24VDC, 230VAC, 400VAC	100 to 3000	0.6 to 70	S1/100%, S3/15%	0.35 to 2.5	54, 65	50	400
	Econorm 01	24VDC, 230VAC, 400VAC	500 to 5000	0.7 to 90	S1/100%, S3/15%	0.25 to 10	54, 65	50	750
	Econorm 1	24VDC, 230VAC, 400VAC	900 to 10000	0.5 to 70	S1/100%, S3/15%	0.8 to 10	54, 65	50	750
	Econorm 2	24VDC, 400VAC	5000 to 20000	1 to 45	S3/15%, S3/60%	1.7 to 16	54, 65	50	750

We are here for you. Addresses and Contacts.

Headquarter Switzerland:

Angst+Pfister Sensors and Power AG
Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:

Angst+Pfister Sensors and Power Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 00
sensorsandpower.de@angst-pfister.com

Scan here and get an overview of personal contacts!



sensorsandpower.angst-pfister.com