



	Flow - Range	Power Supply	Pipe	Operation Temperature	Type
	<b>SQ-FM2PA61-10M</b> 0,3 to 30 l/min Flow Detection < 0,3 l/min is possible	3,0 to 3,3 Vcc / typ. < 30 mA	DN10; Pipe Material PA61	5 °C to 60 °C	Flow-Module
	<b>SQ-FM2PA61-10EK</b> 0,3 to 30 l/min Flow Detection < 0,3 l/min is possible	3,0 to 3,3 Vcc / typ. < 30 mA	DN10; Pipe Material PA61	5 °C to 60 °C	Evaluation-Kit

## We are here for you. Addresses and Contacts.

---

Headquarter Switzerland:

Angst+Pfister Sensors and Power AG  
Thurgauerstrasse 66  
CH-8050 Zurich  
Phone +41 44 877 35 00  
sensorsandpower@angst-pfister.com

Office Germany:

Angst+Pfister Sensors and Power Deutschland GmbH  
Edisonstraße 16  
D-85716 Unterschleißheim  
Phone +49 89 374 288 87 00  
sensorsandpower.de@angst-pfister.com

Scan here and get an overview of personal contacts!



[sensorsandpower.angst-pfister.com](https://sensorsandpower.angst-pfister.com)