

	Notamment	Style	Input Voltage [VAC]	Conformities	Dimensions LxWxH [mm]
	IRL-CL2-01	LED Strip			
	IRL-RGB-01	LED Strip			
	IRL-RGBW-01	LED Strip			
	NCL-CL1-01	LED Strip			
	RFP-M1M3-3A	Wireless diming remote controller			
	RFP-M2M3-3A	Wireless diming remote controller			
	RFP-M5M3-3A	Wireless diming remote controller			
	RFP-M8M4-5A	Wireless RGB remote controller			

		Notamnent	Style	Input Voltage [VAC]	Conformities	Dimensions LxWxH [mm]
	RHP-1U-A	19" Rack for RCP-1600 / RCB-1600				
	POB-30H	Driverless Modular LED Light				
	DRP-01A	Fix Plate for Power Supply				
	SBP-001	Smart battery charger programmer for MW's programmable battery charger series				
	SDP-001	Smart Timer Dimming Programmer for Mean Well LED driver				
	SPD-20	20kA Surge Protection Device, Line to ground, Line to Line protected, LED Status Indicator, IP67	Boxed	240~277	TÜV, UL	90 x 70 x 50
	DAP-04	DALI to PWM Signal Converter, 4 Channels with 4 DALI addresses, Push-Dim, up to 20 Power supplies per channel, Dimming 1~100%, Channels independently dimmable, Class II, IP20	Boxed	90~305	TUV, CE	165 x 46 x 23



DAP-04-S01

DALI to PWM Signal Converter, 4 Channels with 4 or 1 DALI address selectable, Push-Dim, up to 20 Power supplies per channel, Dimming 1~100%, Channels independently dimmable, Class II, IP20

Boxed

90~305

TUV, CE

165 x 46 x 23

	Notamment	Style	Input Voltage [VAC]	Conformities	Dimensions LxWxH [mm]	
	SPD-10S-277S	LED Driver Surge Protection Device; IP66; 120-270VAC at 10kA	Boxed	120~277	UL,DEKRA	46.36x56.76x26

We are here for you. Addresses and Contacts.

Headquarter Switzerland:

Angst+Pfister Sensors and Power AG
Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:

Angst+Pfister Sensors and Power Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 00
sensorsandpower.de@angst-pfister.com

Scan here and get an overview of personal contacts!



sensorsandpower.angst-pfister.com