		Temperature range	Voltage range	Precision	Package
	**SMT172-TO18**	-45 °C ... 130 °C	2.7V ... 5.5V, typ. 3.3V	±0.04 °C (see datasheet);±0.06 °C (10 °C ... 40 °C); ±0.1 °C (-20 °C ... 60 °C); ±0.25 °C (-10 °C ... 100 °C)	TO-18
	**SMT172-TO92**	-45 °C ... 130 °C	2.7V ... 5.5V, typ. 3.3V	±0.35 °C (-10 °C ... 100 °C) ±0.25 °C (-20 °C ... 60 °C)	TO-92
	**SMT172-TO220**	-45 °C ... 130 °C	2.7V ... 5.5V, typ. 3.3V	±0.35 °C (-10 °C ... 100 °C) ±0.25 °C (-20 °C ... 60 °C)	TO-220
	**SMT172-SOIC**	-45 °C ... 130 °C	2.7V ... 5.5V, typ. 3.3V	±0.35 °C (-10 °C ... 100 °C) ±0.25 °C (-20 °C ... 60 °C)	SOIC-8L
	**SMT172-SOT223**	-45 °C ... 130 °C	2.7V ... 5.5V, typ. 3.3V	±0.35 °C (-10 °C ... 100 °C) ±0.25 °C (-20 °C ... 60 °C)	SOT-223
	**SMT172 Evaluation board SMTAS04USB mini**	-45 °C ... 130 °C	2.7V ... 5.5V, typ. 3.3V	±0.25 °C (-10 °C ... 100 °C); ±0.1 °C (-20 °C ... 60 °C)	TO-18
	**MVH4000D**	-40 °C ... 125 °C	1.7V ... 3.6V, typ. 3.3V		

Angst+Pfister
Sensors and Power

We are here for you. Addresses and Contacts.

Headquarter Switzerland:

Angst+Pfister Sensors and Power AG
Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:

Angst+Pfister Sensors and Power Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 00
sensorsandpower.de@angst-pfister.com

Scan here and get an overview of personal contacts!

sensorsandpower.angst-pfister.com