

Solid State Pressure Sensor


ANALOG
OUTPUT



CCD Series – Model 54A

FEATURES

- DIP or SMD Package
- Calibrated Span and Offset
- Multi-order Temperature compensation
- Multi choice of output
- 3V or 5V Supply
- Customized Configuration upon request



DESCRIPTION

The Series CCD Model 54A is a smart pressure transducer with ratiometric analog output. Digital compensation of sensor offset, sensitivity, temperature drift and nonlinearity is accomplished in factory via an internal DSP running a correction algorithm with calibration coefficients stored in on-chip EEPROM.

A variety of characteristic configuration, including accuracy, sampling rate, temperature compensated range are available to provide simple and ready-to-use solution for a wide range of application. It can be operated in supply voltage of 3V or 5V, and can be extended to 30V with an external JFET.

The Series CCD 54A is available for pressure range from 0.15 psi to 150 psi. Special configuration as low as 2.5 mbar is also applicable. Please contact factory for detail.

Ordering Information

Series CCD 54 Analog

54A L - XXX G - X 0 X X

Series

Supply Voltage

Blank = 4.75 to 5.25 V
L = 2.75 to 3.33 V

Pressure range

Medium Pressure

003 = 0 ~ 3 psi

005 = 0 ~ 5 psi

007 = 0 ~ 7 psi

015 = 0 ~ 15 psi

030 = 0 ~ 30 psi

050 = 0 ~ 50 psi

100 = 0 ~ 100 psi

150 = 0 ~ 150 psi

Low Pressure

L15 = 0 ~ 0.15 psi

L30 = 0 ~ 0.3 psi

L50 = 0 ~ 0.5 psi

L70 = 0 ~ 0.7 psi

Ultra-low Pressure

L03 = 0 ~ 2.5 mbar

L07 = 0 ~ 5 mbar

Notes:

Custom ranges and units are available upon request. Please contact factory.

Type of Pressure

G: Gage (Port B only)

H: Gage (Dual Port)

A: Absolute (Port A only)

D: Differential

I: Negative Gage (Port B only)

Option


10: No special request

97: Compensated Temp 0~85 degC


Other options available upon request.

Leading Direction


1= Leads opposite side as Port A



2= Leads same side as Port A



3= J-bend Leads same side as Port A



1. Port B is used for positive differential
2. Port A is used for absolute
3. Port B is used for gage

Type of Output

0 = 1-wire P

1 = 1-wire P+T

2 = 0.5 to 4.5 V

3 = 0.2 to 4.8 V

4 = N/A

5 = 0 to 1 V

6 = 0.2 to 4.7 V

7 = N/A

8 = I²C

9 = SPI

S = Special

NOTES:

1. Specifying differential pressure means a \pm pressure range.
2. Differential pressure can be specified to a maximum of +/- 150 psi.
3. Custom output, pressure range and temperature compensated range are available.
4. Negative gage normally has offset (0.5V) at 0 psi and full scale output (4.5V). Reverse is also applicable.
5. Accuracy may vary on pressure range
6. Minimum absolute pressure that can be specified is 15 psia
7. Medium is available for clean air. For other medium please contact factory.

Characteristics






Unless otherwise specified, all parameters are measured at 3/5V, 25 °C and 60% RH

Parameters	Min	Typ	Max	Unit
Supply Voltage ¹	2.75		5.25	V
Supply Current ¹		2.5		mA
Pressure Range ²	3		150	PSI
Zero Output ⁴	0.428	0.50	0.572	V
Span Output ⁴		4.00		V
Accuracy ³			1.8	%FS
Linearity ³	-0.5		+0.5	%FS
Thermal Hysteresis ³	-0.15		+0.15	%FS
Response Time		1	2	ms
Over Pressure ⁵			3X	Rated Pressure
Temp - Compensating	0		+50	°C
Temp - Operating	-20		+85	°C
Temp - Storage	-40		+125	°C

NOTES:

- Supply 3V or 5V must be ordered separately.
- Smaller range and other units are also available for ordering
- Accuracy includes NOL, hysteresis, TCS and TCO over 0/50°C, BFSL definition
- For differential, offset = 2.50V, Span = ±2.00V
- 1.2X for 150 psi
- Wetted material: PA, RTV, Epoxy, ceramic, Au, nickel and silicon
- Output is ratiometric to supply voltage
- Output load resistance to Vss or Vdd: 2.5KΩ (min), 10KΩ (typ)

Dimension



NOTE:

- Port B is used for positive differential
- Port A is used for absolute
- Port B is used for gage
- All dimensions are mm
- Tube Size: Tygon tube, 4 (o.d.) 2.5 (i.d.) mm

Pin #	Description
1	N.C.
2	V _{SS}
3	OUT
4	V _{DD}
5~8	N.C.

NOTES:

- N.C. pins must be left floating
- A 0.1µf capacitor must be connected between V_{DD} and V_{SS}
- Package : 12 pcs/tube

Characteristics






Unless otherwise specified, all parameters are measured at 3/5V, 25 °C and 60% RH

Parameters	Min	Typ	Max	Unit
Supply Voltage ¹	2.75		5.25	V
Supply Current ¹		2.5		mA
Pressure Range ²	0.15		3	PSI
Zero Output ⁴	0.412	0.50	0.588	V
Span Output ⁴		4.00		V
Accuracy ³			2.2	%FS
Linearity ³	-0.5		+0.5	%FS
Thermal Hysteresis ³	-0.15		+0.15	%FS
Response Time		1	2	ms
Over Pressure ⁵			3X	Rated Pressure
Temp - Compensating	0		+50	°C
Temp - Operating	-20		+85	°C
Temp - Storage	-40		+125	°C

NOTES:

- Supply 3V or 5V must be ordered separately.
- Smaller range and other units are also available for ordering
- Accuracy includes NOL, hysteresis, TCS and TCO over 0/50°C, BFSL definition
- For differential, offset = 2.50V, Span = ±2.00V
- Over-pressure will vary on different range
- Wetted material: PA, RTV, Epoxy, ceramic, Au, nickel and silicon
- Output is ratiometric to supply voltage
- Output load resistance to Vss or Vdd: 2.5KΩ (min), 10KΩ (typ)
- Zeroing at installation is required

Dimension



NOTE:

- Port B is used for positive differential
- Port A is used for absolute
- Port B is used for gage
- All dimensions are mm
- Tube Size: Tygon tube, 4 (o.d.) 2.5 (i.d.) mm

Pin #	Description
1	N.C.
2	V _{SS}
3	OUT
4	V _{DD}
5~8	N.C.

NOTES:

- N.C. pins must be left floating
- A 0.1µf capacitor must be connected between V_{DD} and V_{SS}
- Package : 12 pcs/tube

Characteristics






Unless otherwise specified, all parameters are measured at 3/5V, 25 °C and 60% RH

Parameters	Min	Typ	Max	Unit
Supply Voltage ¹	2.75		5.25	V
Supply Current ¹		2.5		mA
Pressure Range ²	3		150	PSI
Zero Output ⁴	0.428	0.50	0.572	V
Span Output ⁴		4.00		V
Accuracy ³			1.8	%FS
Linearity ³	-0.5		+0.5	%FS
Thermal Hysteresis ³	-0.15		+0.15	%FS
Response Time		1	2	ms
Over Pressure ⁵			3X	Rated Pressure
Temp - Compensating	0		+85	°C
Temp - Operating	-20		+85	°C
Temp - Storage	-40		+125	°C

NOTES:

- 1. Supply 3V or 5V must be ordered separately.
- 2. Smaller range and other units are also available for ordering
- 3. Accuracy includes NOL, hysteresis, TCS and TCO over 0/50°C, BFSL definition
- 4. For differential, offset = 2.50V, Span = ±2.00V
- 5. 1.2X for 150 psi
- 6. Wetted material: PA, RTV, Epoxy, ceramic, Au, nickel and silicon
- 7. Output is ratiometric to supply voltage
- 8. Output load resistance to Vss or Vdd: 2.5KΩ (min), 10KΩ (typ)

Dimension



NOTE:

- 1. Port B is used for positive differential
- 2. Port A is used for absolute
- 3. Port B is used for gage
- 4. All dimensions are mm
- 5. Tube Size: Tygon tube, 4 (o.d.) 2.5 (i.d.) mm

Pin #	Description
1	N.C.
2	V _{SS}
3	OUT
4	V _{DD}
5~8	N.C.

NOTES:

- N.C. pins must be left floating
- A 0.1µf capacitor must be connected between V_{DD} and V_{SS}
- Package : 12 pcs/tube

Headquarter Switzerland:
Angst+Pfister Sensors and Power AG

Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:
Angst+Pfister Sensors and Power
Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 0
sensorsandpower.de@angst-pfister.com



We are here for you. Addresses and Contacts.

Sales Germany & Austria

Geometrical sensors
Other products

Kurt Stritzelberger
Phone +49 89 374 288 87 22
kurt.stritzelberger@angst-pfister.com

Pressure sensors
Other products

Gerhard Vetter
Phone +49 89 374 288 87 26
gerhard.vetter@angst-pfister.com

Gas sensors and modules

Peter Felder
Phone +41 44 877 35 05
peter.felder@angst-pfister.com

Sales Switzerland & Liechtenstein

Postcode 3000 – 9999

Basil Frei
Phone +41 44 877 35 18
basil.frei@angst-pfister.com

Postcode 1000 – 2999

Christian Mohrenstecher
Phone +41 76 444 57 93
christian.mohrenstecher@angst-pfister.com

Sales International Key Accounts

Peter Felder
Phone +41 44 877 35 05
peter.felder@angst-pfister.com

Sales Other Countries / Product Management

Pressure Sensors
Load Cells

Philipp Kistler
Phone +41 44 877 35 03
philipp.kistler@angst-pfister.com

Gas sensors
Gas sensor modules

Dr. Thomas Clausen
Phone +49 89 374 288 87 24
thomas.clausen@angst-pfister.com

Flow / Level / Medical products

Dr. Adriano Pittarelli
Phone +49 89 374 288 87 67
adriano.pittarelli@angst-pfister.com

Power supplies

Sebastiano Leggio
Phone +41 44 877 35 06
sebastiano.leggio@angst-pfister.com

Linear position sensors
Angle sensors

Eric Letsch
Phone +41 44 877 35 14
eric.letsch@angst-pfister.com

Accelerometers
Sensor elements

Christoph Kleye
Phone +49 89 374 288 87 61
christoph.kleye@angst-pfister.com

Drive technology
CH Postcode 5000 – 9999 / DE

Roman Homa
Phone +41 76 444 00 86
roman.homa@angst-pfister.com

Drive technology
CH Postcode 1000 – 4999 / AT / IT / FR

Christian Mohrenstecher
Phone +41 76 444 57 93
christian.mohrenstecher@angst-pfister.com

Harald Thomas
Phone +49 89 374 288 87 23
harald.thomas@angst-pfister.com