

Board Level Pressure Sensors Digital Output


14-Bit, Pressure Sensors

Product	Pressure Range	Op. Temp. [°C]	Accuracy [%FS]	Total Error [%FS]	Size [mm]	Typical Application
Differential/Gage Pressure, barbed pressure ports, 3.3V or 5V, 3mA, 1.5ms conversion time, I²C+SPI interface						
MS4515DO	2, 4, 5, 10, 20, 30 in H ₂ O	-10 to +85	±0.25	±1.0	12.45 x 9.90	Blocked Filter Detection, Medical Instruments
MS4525DO	1, 5, 15, 30, 50, 100, 150psi	-25 to +105	±0.25	±1.0	12.45 x 9.90	Factory Automation, Medical Instruments



16-Bit, Ultra Low Power Pressure Sensors

Product	Pressure Range	Op. Temp. [°C]	Resolution [mbar]	Error [mbar]	Size [mm]	Typical Application
Absolute Pressure, 2.2 to 3.6V, 5uA, 35ms conversion time, SPI compatible interface						
MS5534CP	10 to 1100mbar	-40 to +125	0.1	±1.5	9 x 9	Indoor Barometer/Altimeter
MS5534CM						Outdoor Barometer/Altimeter
MS5535C	14bar	-40 to +125	1.2	±25	9 x 9	Diving Computer 130m
MS5535-30C	30bar					Diving Computer 300m
MS5540CM	10 to 1100mbar	-40 to +85	0.1	±1.5	6.2 x 6.4	Altimeter Watch, Bike Computer
MS5541CM	14bar	-40 to +85	1.2	±25	6.2 x 6.4	Diving Watch 130m
MS5561BM	1bar	-40 to +85	0.1	±1.5	4.25 x 4.75	GPS Altimeter
Differential/Gage Pressure						
MS5536-60	60mbar	-40 to +85	0.05	±1.0	10 x 13	Airspeed Measurement
MS5536-CPJU	-400 to +1000mbar	-40 to +85	0.1	±2.5	10 x 13	CPAP, Sleep Apnea, Airspeed, Blood Pressure
MS5536-CJJU	-1000 to +400mbar					



24-Bit, Ultra Low Power Pressure Sensors

Product	Pressure Range	Op. Temp. [°C]	Resolution [mbar]	Error [mbar]	Size [mm]	Typical Application
Absolute Pressure, <u>no gel</u>, 1.8 to 3.6V, 1uA, 0.5 to 8.2ms conversion time, I²C+SPI interface, internal clock						
MS5605-02BA	2bar	-40 to +85	0.024	±5	5 x 3 x 1.6	Weather Stations
MS5607-02BA	10 to 1200mbar	-40 to +85	0.024	±1.5	5 x 3 x 1	GPS Altimeters, Mobile Phones
MS5611-01BA	like MS5607-BP but with double resolution of 0.012mbar, for variometers					
Absolute Pressure, <u>gel-filled</u>, for outdoor products						
MS5803-01BA	10 to 1300mbar		0.012	±1.5		Altimeter Watch, Bike Computer
MS5803-02BA	10 to 2000mbar		0.024	±3.0		Altimeter Watch, Bike Computer
MS5803-05BA	5bar	-40 to +85	0.036	±4.5	6.2 x 6.4	Dual Range Altimeter/Diving
MS5803-14BA	14bar		0.15	±20		Diving Watch 130m
MS5803-30BA	30bar		0.36	±50		Diving Watch 300m
MS5805-02BA	10 to 2000mbar	-40 to +85	0.024	±3.0	4.5 x 4.5	Miniature Altimeter Watch
Absolute/Differential Pressure, high resolution						
MS4515HRD	2, 4, 5, 10, 20, 30 in H ₂ O	-10 to +85	0.001 to 0.005	±0.1 to ±0.5	12.45 x 9.90	Blocked Filter Detection, Medical Instruments
MS4525HRD	1, 5, 15, 30, 50, 100, 150psi	-25 to +105	0.005 to 0.15	±0.25	12.45 x 9.90	High Precision Medical Instruments



a= absolute pressure, g= gage pressure, d=differential pressure

Board Level Pressure Sensors Analog Output

Amplified & Compensated Output

Product	Pressure Range	Op. Temp. [°C]	Accuracy [%FS]	Total Error [%FS]	Size [mm]	Typical Application
Differential/Gage Pressure, barbed pressure ports, 3.3V or 5V, 3mA, ratiometric analog output voltage						
MS4515	2, 4, 5, 10, 20, 30 in H ₂ O	-10 to +85	±0.25	±1.0	12.45 x 9.90	Blocked Filter Detection, Medical Instruments
MS4525	1, 5, 15, 30, 50, 100, 150psi	-25 to +105	±0.25	±1.0	12.45 x 9.90	Factory Automation, Medical Instruments



mV Output

Product	Pressure Range	Op. Temp. [°C]	Span [mV/5V]	Linearity [%FS]	Size [mm]	Feature
SMD Uncompensated						
1451	5, 15, 30, 50, 100, 250, 500psi	-40 to +125	60	±0.25	7.6 x 7.6	Tube, Narrow Hole, Wide Hole
MS52XX	1, 12bar	-40 to +125	150	± 0.05	7.6 x 7.6	High Linearity, High Sensitivity Option
			240	± 0.15		
MS54XX	1, 7, 12bar	-40 to +125	150	±0.05	6.2 x 6.4	Gel-filled, Waterproof, for Sealing with O-Ring
			240	±0.15		
			392	±0.3		
SMD compensated						
1471	5, 15, 30, 50, 100, 250, 500psi	-40 to +125	65	±0.25	7.6 x 7.6	Tube, Narrow Hole, Wide Hole
DIL compensated						
1210	5, 10 in H ₂ O	-40 to +125	50mV & 100mV	±0.1	15.2 x 20.3	Temperature Compensated
1220						Ultra Stable (1230/40)
1230						Current Ex. (1210/30)
1240						Voltage Ex. (1220/40)



Silicon Die (OEM)

Product	Pressure Range	Op. Temp. [°C]	Span [mV/5V]	Linearity [%FS]	Size [mm]	Feature
MS7305-D	50mbar	-40 to +125	110	± 0.3	2.45 x 2.45	Low Pressure, High Output Signal, Low Position Sensitivity
MS7310-D	100mbar		110	± 0.35	2.45 x 2.45	
MS763	400mbar		22.5	±0.15	1.30 x 2.20	Medical Die, for Catheters
MS764	400mbar		180	±0.15	1.96 x 2.10	Medical, Industrial
MS765	500mbar	-40 to +125	170	±0.05	1.96 x 2.10	Low Pressure, High Linearity
MS761	1bar		240	±0.15	1.96 x 2.10	High Sensitivity
MS767	7bar		392	±0.15	1.98 x 1.84	Very High Sensitivity
MS78xx	1, 12bar	-40 to +125	150	±0.05	2.10 x 1.96	Standard, High Linearity
MS79xx	0.5, 1, 2, 4, 7, 12, 30, 70bar	-40 to +125	150	±0.05	1.78 x 1.78	Miniature, High Linearity
					1.72 x 1.58	
MS7212-A	12bar	-40 to +125	150	±0.05	1.63 x 1.95	Harsh Media, Automotive Qualified, Routing Compatible to MS79xx
MS7228-A	28bar		150	±0.05	1.63 x 1.95	
MS7201-A2	1bar		110	±0.15	1.35 x 1.79	
MS7212-A2	12bar	-40 to +150	150	±0.05	1.18 x 1.73	Harsh Media, Automotive Qualified, for Die-to-Die Bonding, Temperature Diode Integrated
MS7218-A2	18bar		150	±0.05	1.18 x 1.73	
MS7236-A2	36bar		150	±0.05	1.18 x 1.73	
P6393	2, 5, 10, 15, 30, 50, 250, 500psi	-50 to +150	110	±0.1	3.00 x 4.00	High Sensitivity, High Reliability
P7405	1000, 3000, 5000psi	-40 to +125	150	±0.25	1.86 x 2.10	High Pressure, Open Bridge

a= absolute pressure, g= gage pressure, d=differential pressure

Headquarter Switzerland:
Angst+Pfister Sensors and Power AG

Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:
Angst+Pfister Sensors and Power
Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 0
sensorsandpower.de@angst-pfister.com



We are here for you. Addresses and Contacts.

Sales Germany & Austria

Geometrical sensors
Other products

Kurt Stritzelberger
Phone +49 89 374 288 87 22
kurt.stritzelberger@angst-pfister.com

Pressure sensors
Other products

Gerhard Vetter
Phone +49 89 374 288 87 26
gerhard.vetter@angst-pfister.com

Gas sensors and modules

Peter Felder
Phone +41 44 877 35 05
peter.felder@angst-pfister.com

Sales Switzerland & Liechtenstein

Postcode 3000 – 9999

Basil Frei
Phone +41 44 877 35 18
basil.frei@angst-pfister.com

Postcode 1000 – 2999

Christian Mohrenstecher
Phone +41 76 444 57 93
christian.mohrenstecher@angst-pfister.com

Sales International Key Accounts

Peter Felder
Phone +41 44 877 35 05
peter.felder@angst-pfister.com

Sales Other Countries / Product Management

Pressure Sensors
Load Cells

Philipp Kistler
Phone +41 44 877 35 03
philipp.kistler@angst-pfister.com

Gas sensors
Gas sensor modules

Dr. Thomas Clausen
Phone +49 89 374 288 87 24
thomas.clausen@angst-pfister.com

Flow / Level / Medical products

Dr. Adriano Pittarelli
Phone +49 89 374 288 87 67
adriano.pittarelli@angst-pfister.com

Power supplies

Sebastiano Leggio
Phone +41 44 877 35 06
sebastiano.leggio@angst-pfister.com

Linear position sensors
Angle sensors

Eric Letsch
Phone +41 44 877 35 14
eric.letsch@angst-pfister.com

Accelerometers
Sensor elements

Christoph Kleye
Phone +49 89 374 288 87 61
christoph.kleye@angst-pfister.com

Drive technology
CH Postcode 5000 – 9999 / DE

Roman Homa
Phone +41 76 444 00 86
roman.homa@angst-pfister.com

Drive technology
CH Postcode 1000 – 4999 / AT / IT / FR

Christian Mohrenstecher
Phone +41 76 444 57 93
christian.mohrenstecher@angst-pfister.com

Harald Thomas
Phone +49 89 374 288 87 23
harald.thomas@angst-pfister.com