

# DATASHEET

## Pressure Sensor SPD030GAsilUBS

last update  
October 5, 2016

reference  
spd030gasilubs n

page  
1/1

### DIFFERENTIAL PRESSURE SENSOR WITH COMPENSATED ANALOGUE OUTPUT




This Smartec pressure sensor has an amplified analogue output. The sensor is compensated for offset, sensitivity, temperature drift and nonlinearity. The sensor is calibrated on 30 PSI. The output is ratiometric to the power supply voltage.



#### Electrical Characteristics

Parameter	Min	Typ	Max	Units
Supply Voltage	4.75	5.00	5.25	V
Supply Current	-	2,5		mA
Pressure range (fs)	0		30	psi
Zero Output (0 psi)	0,119	0,2	0,281	Vdc
Full scale output (@30 PSI)		4,9		Vdc
Accuracy			1,8	%FS
Linearity	-0,5		0,5	%FS
Thermal Hysteresis	-0,15		0,15	%FS
Response time		1	2	ms
Overpressure			2x	Rated pressure
Temp compensation	0		50	°C
Operating Temp range	-20		70	°C
Storage temperature	-40		125	°C

- Accuracy includes all errors ( 0 - 50 °C)
- Wetted material contains RTV, PPA, glass and silicon



Pin#	description
1	Vcc.
2	GND
3	OUT
4	Gnd
5	N.C

All sizes in mm

Use of N.C. pins will cause malfunction

Connect between Vcc and Gnd a capacitor of 100 nF



## We are here for you. Addresses and Contacts.

---

### Headquarter Switzerland:

Angst+Pfister Sensors and Power AG  
Thurgauerstrasse 66  
CH-8050 Zurich  
Phone +41 44 877 35 00  
[sensorsandpower@angst-pfister.com](mailto:sensorsandpower@angst-pfister.com)

### Office Germany:

Angst+Pfister Sensors and Power Deutschland GmbH  
Edisonstraße 16  
D-85716 Unterschleißheim  
Phone +49 89 374 288 87 00  
[sensorsandpower.de@angst-pfister.com](mailto:sensorsandpower.de@angst-pfister.com)

---

Scan here and get an overview of personal contacts!



[sensorsandpower.angst-pfister.com](https://sensorsandpower.angst-pfister.com)

---