

Solutions by Sensor type:

Force

Force

Measurement Specialties has been a pioneer in the design and manufacture of ultra-low cost OEM load cells. Initially designed for use in high-volume digital bathroom scales, MEAS has developed a line of low cost load cells that allow OEMs across a variety of industries to incorporate direct force measurement into their products. Based on our proprietary piezoresistive silicon strain gauge (Microfused™) technology, our load cells combine outstanding durability and long term stability in an extremely low cost package, perfectly suited for medium and high volume applications.

Our load cells are tailored for the specific customer application, including custom packaging and electronics with analog or digital outputs, suited for both low and high force environments.



Load Cells

Low cost OEM load cells



FX 1901-0001



FS20



FC22



FC23

Package	Low profile "coin cell" design	Miniature; drop in replacement for industry standard	Plastic housing, button, flange mounting	Stainless steel housing button shape for higher weight loads
Operating Mode	Compression	Compression	Compression	Compression
Unique Feature	Ultra low cost, low strain design: essentially unlimited cycle life	Load cell design operates at very low strains; not subject to lead die fatigue	Low cost button shape essentially unlimited cycle life	Industry standard low profile all stainless steel design. Resistant to off-axis loads.
Ranges (Lbf)	10, 25, 50, 100	1.5, 3	25, 50, 100	250, 500, 1000, 2000
Max Overload	2.5X	10 lbf	2.5X	1.5X and 2.5X
Output / Span	100mV	1.0 to 4.0V	100mV, 0.5 to 4.5Vdc	100mV
Combined Linearity Hysteresis	±1.0% FSO	±1.0% FSO	±1.0% FSO	±1.0% FSO
Operating Temp	-40° to 85°C	0° to 70°C	-40° to 85°C	-40° to 85°C
Typical Apps	Consumer OEM, exercise machines, physical therapy, vending machines, appliances, pumps, medical devices	Infusion pumps, contact sensing, medical devices, consumer appliances	Infusion pumps, robotics end-effectors, exercise machines, contact sensing, appliances	Batch weighing, robotics, assembly line force, printing presses, pumps, winch & hoist
Legacy Brand	MEAS	MEAS	MEAS	MEAS

Test and Measurement load cells



ELPF, ELFF, ELWF, ELAF



ELHM, ELHS



EL20-S458

Package	Dual Stud, Button, Through hole	High capacity dual stud or button style	Special purpose design optimized for automotive crash test environments
Operating Mode	Tension and Compression	Tension and Compression	Tension
Unique Feature	- High immunity to off axis loads - Low deflection design for fast response and high cycle life - Optional external amplifier module - NIST traceable calibration provided	- Tension and compression or compression only - High stability metal foil strain gage (ELHM) - High output semiconductor strain gage (ELHS) - NIST traceable calibration provided	- Low mass titanium design for use in high shock environments - Mass optimized to minimize acceleration induced errors during SAE J2570 ATD testing - Optional high level and linearized outputs - Smoothed edge design and optional slotted titanium axles eliminate drag errors and dummy damage - Ultra robust cable is user replaceable - NIST traceable calibrations provided
Ranges (Lbf)	10 to 5000	200 to 10K	1000 & 3200
Max Overload	2.5X	1.5X	2X
Output / Span	100mV (0.5-4.5V optional)	10mV (ELHM), 200mV FSO (ELHS)	10mV (0.5-4.5V optional)
Non-Linearity	0.25% to 1% FSO	0.3% to 0.5% FSO	1.0% to 3.0% FSO
Operating Temp	-40° to 120°C	-50° to 120°C (ELHM), -20° to 80°C (ELHS)	-40° to 120°C
Applications	Research, materials test, medical instrumentation, physical therapy, weighing, thrust, biomechanical measurements, product validation test	Robust general purpose, low deflection design: machine tool, linkage forces	Seat belt forces, safety and restraint system crash test, parachute tether/riser forces
Legacy Brand	Entran	Entran	Entran



Headquarter Switzerland:
Angst+Pfister Sensors and Power AG

Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:
Angst+Pfister Sensors and Power
Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 0
sensorsandpower.de@angst-pfister.com



We are here for you. Addresses and Contacts.

Sales Germany & Austria

Geometrical sensors
Other products

Kurt Stritzelberger
Phone +49 89 374 288 87 22
kurt.stritzelberger@angst-pfister.com

Pressure sensors
Other products

Gerhard Vetter
Phone +49 89 374 288 87 26
gerhard.vetter@angst-pfister.com

Gas sensors and modules

Peter Felder
Phone +41 44 877 35 05
peter.felder@angst-pfister.com

Sales Switzerland & Liechtenstein

Postcode 3000 – 9999

Basil Frei
Phone +41 44 877 35 18
basil.frei@angst-pfister.com

Postcode 1000 – 2999

Christian Mohrenstecher
Phone +41 76 444 57 93
christian.mohrenstecher@angst-pfister.com

Sales International Key Accounts

Peter Felder
Phone +41 44 877 35 05
peter.felder@angst-pfister.com

Sales Other Countries / Product Management

Pressure Sensors
Load Cells

Philipp Kistler
Phone +41 44 877 35 03
philipp.kistler@angst-pfister.com

Gas sensors
Gas sensor modules

Dr. Thomas Clausen
Phone +49 89 374 288 87 24
thomas.clausen@angst-pfister.com

Flow / Level / Medical products

Dr. Adriano Pittarelli
Phone +49 89 374 288 87 67
adriano.pittarelli@angst-pfister.com

Power supplies

Sebastiano Leggio
Phone +41 44 877 35 06
sebastiano.leggio@angst-pfister.com

Linear position sensors
Angle sensors

Eric Letsch
Phone +41 44 877 35 14
eric.letsch@angst-pfister.com

Accelerometers
Sensor elements

Christoph Kleye
Phone +49 89 374 288 87 61
christoph.kleye@angst-pfister.com

Drive technology
CH Postcode 5000 – 9999 / DE

Roman Homa
Phone +41 76 444 00 86
roman.homa@angst-pfister.com

Drive technology
CH Postcode 1000 – 4999 / AT / IT / FR

Christian Mohrenstecher
Phone +41 76 444 57 93
christian.mohrenstecher@angst-pfister.com

Harald Thomas
Phone +49 89 374 288 87 23
harald.thomas@angst-pfister.com