smartGAS MIKROSENSORIK

blue performance®

smartMODUL BASIC^{EVO}

Infrared gas sensor SF6 // SULFUR HEXAFLUORIDE // 1000 ppm
smartGAS item number: B3-602105-03000



- **Pre calibrated**
- **Gas entry by diffusion**
- **3.3 - 6 V DC supply voltage**
- **Modbus ASCII or RTU**
- **Status indication by LED**

Non Dispersive Infrared (NDIR) gas sensor for ambient air monitoring using dual wavelength technology. Especially designed for the analysis of SF6 quality and purity inside gas insulated switchgears (GIS).

The BASIC^{EVO} SF6 sensor can easily be integrated into OEM systems, where long term stability, repeatability and reliable performance are required. Furthermore, its high-precision NDIR technology also qualifies the BASIC^{EVO} gas sensor for utilisation in numerous laboratory measurements where precision and reliability are of uttermost importance for subsequent processing. Special build-in solutions to provide IP54 protection and easy field gas-calibration are available.

Modbus ASCII or RTU data communication offer a variety of options to connect the BASIC^{EVO} gas sensor to a controller.

APPLICATION EXAMPLE
SF6 PURITY ANALYSING
SF6 QUALITY CONTROL
LABORATORY MEASUREMENTS
HIGH VOLTAGE CABLES
HIGH VOLTAGE TRANSFORMERS

smartGAS Mikrosensorik GmbH | Huenderstr. 1 | 74080 Heilbronn | Germany
phone: +49 7131/797553-0 | fax: +49 7131/797553-10 | www.smartgas.eu | mail@smartgas.eu

Edition 02/08_2017

smartGAS MIKROSENSORIK

smartMODUL BASIC EVO

Infrared gas sensor SF6 // SULFUR HEXAFLUORIDE // 1000 ppm
smartGAS item number: B3-602105-03000

General features	
Measurement principle:	Non Dispersive Infra-Red (NDIR), dual wavelength
Measurement range:	0..1000 ppm Full Scale (FS)
Gas supply:	by diffusion (atmospheric pressure)
Dimensions:	62 mm x 37 mm x 30 mm (L x W x H)
Warm-up time:	< 2 minutes (start up time) < 11 minutes (fade in finished) < 30 minutes (full specification)
Measuring response*	
Response time (t_{90}):	appr. 60 s
Digital resolution (@ zero):	1 ppm
Detection limit (3 σ):	≤ 10 ppm
Repeatability:	≤ ± 15 ppm
Linearity error (straight line deviation):	≤ ± 20 ppm
Long term stability (span):	≤ ± 30 ppm over 12 month period
Long term stability (zero):	≤ ± 25 ppm over 12 month period
Influence of T and P*	
Temp. dependence (zero):	≤ ± 1.5 ppm per °C
Temp. dependence (span):	≤ ± 3 ppm per °C
Pressure dependence:	± 0.100 % of measurement value / hPa
Electrical inputs and outputs	
Supply voltage:	3.3 V .. 6.0 V DC
Supply current (peak):	< 400 mA @ 3.3 V, < 240 mA @ 5.0 V
Inrush current:	< 600 mA
Average power consumption:	< 800 mW
Digital output signal:	Modbus ASCII / RTU via UART, autobaud, autoframe
Calibration:	zero and span by SW
Climatic conditions	
Operating temperature:	-20 .. + 40 °C
Storage temperature:	-20 .. + 60 °C
Air pressure:	800 .. 1150 hPa
Ambient humidity:	0 .. 95 % relative humidity (not condensing)
* Typical values related to 1013 hPa and 22 °C for dry (not condensing) and clean sample gas. Stated values exclude calibration gas tolerance.	

All rights reserved. Any logos and/or product names are trademarks of smartGAS. The reproduction, transfer, distribution or storage of information contained in this brochure in any form without the prior written consent of smartGAS is strictly prohibited. All specifications – technical included – are subject to change without notice. Depending on the application, the target gas and the measurement range the technical data may differ. No liability is accepted for any consequential losses, injury or damage resulting from the use of this document or from any omissions or errors herein. The data is given for guidance only. It does not constitute a specification or an offer for sale.

For more information, please visit www.smartGAS.eu or contact us at sales@smartgas.eu
Please consult smartGAS sales for parts specified with other temperature and measurement ranges. At first initiation and depending on application and ambient conditions recalibration is recommended. Recurring cycles of recalibration are recommended.

smartGAS Mikrosensorik GmbH | Huenderstr. 1 | 74080 Heilbronn | Germany
phone: +49 7131/797553-0 | fax: +49 7131/797553-10 | www.smartgas.eu | mail@smartgas.eu

Edition 02/08_2017

Angst+Pfister
Sensors and Power

We are here for you. Addresses and Contacts.

Headquarter Switzerland:

Angst+Pfister Sensors and Power AG
Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:

Angst+Pfister Sensors and Power Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 00
sensorsandpower.de@angst-pfister.com

Scan here and get an overview of personal contacts!

sensorsandpower.angst-pfister.com