

SMART MODUL

FLOW^{EVO} for insulating systems

SF6 Infrared gas sensor for flow with digital interface



- Pre calibrated
- Compact design
- 3/5 mm gas line connectors
- 3,3 - 6 V DC supply voltage
- Modbus ASCII or RTU
- Status indication by LED

Infrared gas sensor for process control and gas analysing using dual wavelength technology.

Designed for different applications in a wide range of gas measurement systems. The FLOW EVO sensor is easy to be integrated into OEM systems, where long term stability, repeatability and reliable performance are required.

Modbus ASCII or RTU data communication offer a variety of options to connect the PREMIUM4 EVO sensor to a controller.

Atmospheric pressure compensation, on board status LED, temperature compensation, low drift, ready to use calibration, a wide range of different gases and measurement ranges - all that makes the FLOW EVO sensor the best choice also for your application and helps to save time and costs with design in.

FLOW^{EVO} for insulating systems // technical Data

SF6 Infrared gas sensor for flow with digital interface

F3-600105-00900

sulfur hexafluoride SF₆

1.000 ppm

General features	
Model type:	F3-600105-00900
Measurement principle:	Non Dispersive InfraRed (NDIR)
Gas:	sulfur hexafluoride, SF ₆
Measurement range:	0 - 1.000 ppm
Gas supply:	Flow, with pump
Gas line connector:	3 mm internal, 5 mm outer diameter
Flow Rate:	0.2 to 0.8 l / min (const)
Dimensions Sensor:	73 mm x 30 mm x 43 mm (L x H X W)
Warm-up time Start up:	≤ 2 minutes
Warm-up time full spec:	≤ 30 minutes
measuring response ⁽¹⁾	
Response time (t ₉₀): ⁽¹⁾	appr. 15 s (@ 0.5 l/min)
Digital resolution:	1 ppm
Detection limit (3 δ):	≤ 5 ppm (typically)
Repeatability:	≤ ± 5 ppm
Linearity error: ⁽²⁾	≤ ± 10 ppm
Influencing Variable ⁽⁴⁾	
Temp. Dependence (zero):	≤ ± 0.1 % Full scale per °C
Temp. Dependence (span):	≤ ± 0.2 % Full scale per °C
Pressure Dependence (zero):	---
Pressure Dependence (span):	0.1 % value per hPa
Electrical data	
Supply Voltage:	3,3 - 6 V DC
Power Consumption:	< 1 Watt
Digital output:	UART Modbus ASCII / RTU
Unit intervall:	2 400 - 38 400 Baud
Analogue output:	---
Calibration:	zero and span by software
optical display:	Status- and function with LED
Climatic conditions	
Operating temperature:	-10 °C ... + 40 °C
Storage Temperature:	-20 °C ... + 60 °C
Air pressure:	800 to 1 2000 hPa
Humidity:	0 % to 95 % rel. Humidity (not condensing)
Optional Accessories:	Micropump Filter

FLOW^{EVO} for insulating systems // technical Data

SF6 Infrared gas sensor for flow with digital interface

F3-600105-00900


sulfur hexafluoride SF6

1.000 ppm

At first Initiation and depending on application and ambient conditions recalibration is recommended.

Please consult **PEWATRON AG** for parts specified with other temperature and measurement ranges

- 1) Relating to sample gas pressure 1013 hPa absolute, 0.5 l/min gas flow and 25°C ambient and gas temperature
- 2) Stated linearity error excludes calibration gas tolerance of 2%
- 3) For dry and clean test gas at 25°C and 1013 hPa absolute - depending on the operation and ambient conditions values may differ
- 4) Relating to calibration conditions (see final check)



Headquarter Switzerland:
Angst+Pfister Sensors and Power AG

Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:
Angst+Pfister Sensors and Power
Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 0
sensorsandpower.de@angst-pfister.com



We are here for you. Addresses and Contacts.

Sales Germany & Austria

Geometrical sensors
Other products

Kurt Stritzelberger
Phone +49 89 374 288 87 22
kurt.stritzelberger@angst-pfister.com

Pressure sensors
Other products

Gerhard Vetter
Phone +49 89 374 288 87 26
gerhard.vetter@angst-pfister.com

Gas sensors and modules

Peter Felder
Phone +41 44 877 35 05
peter.felder@angst-pfister.com

Sales Switzerland & Liechtenstein

Postcode 3000 – 9999

Basil Frei
Phone +41 44 877 35 18
basil.frei@angst-pfister.com

Postcode 1000 – 2999

Christian Mohrenstecher
Phone +41 76 444 57 93
christian.mohrenstecher@angst-pfister.com

Sales International Key Accounts

Peter Felder
Phone +41 44 877 35 05
peter.felder@angst-pfister.com

Sales Other Countries / Product Management

Pressure Sensors
Load Cells

Philipp Kistler
Phone +41 44 877 35 03
philipp.kistler@angst-pfister.com

Gas sensors
Gas sensor modules

Dr. Thomas Clausen
Phone +49 89 374 288 87 24
thomas.clausen@angst-pfister.com

Flow / Level / Medical products

Dr. Adriano Pittarelli
Phone +49 89 374 288 87 67
adriano.pittarelli@angst-pfister.com

Power supplies

Sebastiano Leggio
Phone +41 44 877 35 06
sebastiano.leggio@angst-pfister.com

Linear position sensors
Angle sensors

Eric Letsch
Phone +41 44 877 35 14
eric.letsch@angst-pfister.com

Accelerometers
Sensor elements

Christoph Kleye
Phone +49 89 374 288 87 61
christoph.kleye@angst-pfister.com

Drive technology
CH Postcode 5000 – 9999 / DE

Roman Homa
Phone +41 76 444 00 86
roman.homa@angst-pfister.com

Drive technology
CH Postcode 1000 – 4999 / AT / IT / FR

Christian Mohrenstecher
Phone +41 76 444 57 93
christian.mohrenstecher@angst-pfister.com

Harald Thomas
Phone +49 89 374 288 87 23
harald.thomas@angst-pfister.com