




# MEMS Sensors & Sensing Elements



⚠Note • Please read rating and ⚠CAUTION (for storage, operating, rating, soldering, mounting and handling) in this catalog to prevent smoking and/or burning, etc.  
• This catalog has only typical specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

S47E.pdf  
Jan.11,2019



## Accelerometers

Murata is the global market leader in low-g acceleration sensors for automotive applications. The extensive accelerometer product range includes high performance analog and digital accelerometers for both safety critical automotive and industrial applications.

Murata accelerometers are based on the company's proprietary 3D MEMS technology and offer a number of excellent product features for the most demanding applications. The sensing element and the measuring ASIC are assembled in dual flat lead plastic package with pins for the surface mount and re-flow soldering. They are environmentally protected with silicone gel, resulting in excellent performance and reliability in humid environments and at temperature cycling. In addition, the robust sensing element design with over damped frequency response enables excellent performance even in harsh and vibrating environments.

Series	No. of axes	Range	Supply voltage	Temperature range	Sensitivity	Signal bandwidth	Output type	Typical applications
SCA800	1	±2 g	3.3 V	-40 ... +125 °C	900 LSB/g	50 Hz	Digital/SPI	Automotive safety critical applications, IMU, Industrial applications
SCA2100	2	±2 g	3.3 V	-40 ... +125 °C	900 LSB/g	45 Hz	Digital/SPI	
SCA3100	3	±2 g ±6 g	3.3 V	-40 ... +125 °C	900 LSB/g 650 LSB/g	45 Hz	Digital/SPI	
SCA3300	3	±3 g ±6 g ±1.5 g	3.3 V	-40 ... +125 °C	2700 LSB/g 1350 LSB/g 5400 LSB/g	70 Hz 70 Hz 70 Hz/10Hz*	Digital/SPI	

\* user selectable via SPI bus



## Inclinometers

Murata inclination sensors are an optimum choice for high accuracy leveling and inclination measurement instruments. Highest accuracy 3-axis inclination measurement is available with Murata's SCL3300. This sensor also features direct inclination angle output making it a perfect choice for variety of different use cases and applications.

With the best shock durability available on the MEMS market, Murata inclinometers provide trouble-free measurements in moving machines, vehicles, airplanes, construction machines and handheld devices.

Series	No. of axes	Range	Supply voltage	Temperature range	Sensitivity	Signal bandwidth	Output type	Typical applications
SCA830	1	±90°, ±1 g	3.3 V	-40 ... +125 °C	32000 LSB/g	6.25 Hz	Digital/SPI	Levelling, Tilt sensing, Machine control, Structural health monitoring, Inertial measurement units (IMUs), Robotics, Positioning and guidance systems
SCL3300	3	±1.8g/±90°	3.3 V	-40 ... +125 °C	6000 LSB/g/*182 LSB/°	40 Hz	Digital/SPI	
		±3.6g/±90° - /±10°			3000 LSB/g/*182 LSB/° 12000 LSB/g/*182 LSB/°	70 Hz 10 Hz		


\* Inclination output

Murata Electronics Oy's product range also includes inclination modules and sub-assemblies. For more information, please refer to the product datasheets available online at [www.murata.com](http://www.murata.com)

**muRata**

⚠Note • Please read rating and ⚠CAUTION (for storage, operating, rating, soldering, mounting and handling) in this catalog to prevent smoking and/or burning, etc.  
• This catalog has only typical specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

S47E.pdf  
Jan.11,2019



## Gyroscopes

Murata develops and manufactures gyroscope components based on the company's proven 3D MEMS technology and highly integrated electronics.

Industrial gyros offer a performance level that typically has been available only for expensive module products. The sensing elements and measuring circuitry are assembled into a premolded plastic dual-in-line (DIL) package, protected with silicon gel and covered with a stainless steel lid. All products are RoHS compatible and suitable for lead-free reflow soldering.

Series	No. of axes	Range	Supply voltage	Temperature range	Sensitivity	Signal bandwidth	Output type	Typical applications
SCC1300	X-axis gyro 3-axis accelerometer	$\pm 100^\circ/\text{s}$ , $\pm 2\text{ g}$ $\pm 300^\circ/\text{s}$ , $\pm 6\text{ g}$	5 V analog 3.3 V digital	-40 ... +125 °C	50 LSB/(°/s), 1800 LSB/g, 18 LSB/(°/s), 650 LSB/g	50 Hz	Digital/SPI	Platform stabilization, Motion analysis and control, Guidance and navigation systems
SCR1100	X-axis gyro	$\pm 100^\circ/\text{s}$ $\pm 300^\circ/\text{s}$	5 V analog 3.3 V digital	-40 ... +125 °C	50 LSB/(°/s) 18 LSB/(°/s)	50 Hz	Digital/SPI	
SCC2130	X-axis gyro 3-axis accelerometer	$\pm 125^\circ/\text{s}$ , $\pm 6\text{ g}$	3.3 V	-40 ... +125 °C	50 LSB/(°/s) 1962 LSB/g	60 Hz/10 Hz*	Digital/SPI	
SCR2100	X-axis gyro	$\pm 125^\circ/\text{s}$	3.3 V	-40 ... +125 °C	50 LSB/g	60 Hz/10 Hz*	Digital/SPI	
SCC2230	Z-axis gyro 3-axis accelerometer	$\pm 125^\circ/\text{s}$ , $\pm 6\text{ g}$ $\pm 125^\circ/\text{s}$ , $\pm 2\text{ g}$	3.3 V	-40 ... +125 °C	50 LSB/(°/s) 1962 LSB/g (6 g) 5886 LSB/g (2 g)	60 Hz/10 Hz*	Digital/SPI	

\* User selectable via SPI bus



## Pressure Sensing Elements

Murata SCB10H capacitive absolute pressure sensing elements have been designed for applications that require a small size and ultra low power consumption. The SCB10H pressure sensing elements are ideal for implantable medical devices thanks to their inherent accuracy, reliability, small size and enabled low power consumption.

The SCB10H pressure sensing element allows the possibility for volume OEM customers to integrate pressure measurement functions in an optimal way into their products.

Parameter	Unit	B012	B080	B250	Typical applications
Measuring range	kPa	30–120	100–800	100–2500	Medical devices, Flow meters, Barometers, Altimeters
Capacitance at min. pressure	pF	7.8	7.5	7.3	
Capacitance at max. pressure	pF	11.8	13.4	13.9	
Capacitance dynamics	pF	4.0	5.9	6.6	
Sensitivity	fF/kPa	55 (@100 kPa)	6.2 (@350 kPa)	1.3 (@100 kPa) 6.5 (@2500 kPa)	

For more information, please refer to the product datasheets available online at [www.murata.com](http://www.murata.com)

**MURATA**

# Global Locations

For details please visit [www.murata.com](http://www.murata.com)



## Note

### 1 Export Control

#### For customers outside Japan:

No Murata products should be used or sold, through any channels, for use in the design, development, production, utilization, maintenance or operation of, or otherwise contribution to (1) any weapons (Weapons of Mass Destruction [nuclear, chemical or biological weapons or missiles] or conventional weapons) or (2) goods or systems specially designed or intended for military end-use or utilization by military end-users.

#### For customers in Japan:

For products which are controlled items subject to the "Foreign Exchange and Foreign Trade Law" of Japan, the export license specified by the law is required for export.

2 Please contact our sales representatives or product engineers before using the products in this catalog for the applications listed below, which require especially high reliability for the prevention of defects which might directly damage a third party's life, body or property, or when one of our products is intended for use in applications other than those specified in this catalog.

- ① Aircraft equipment
- ② Aerospace equipment
- ③ Undersea equipment
- ④ Power plant equipment
- ⑤ Medical equipment
- ⑥ Transportation equipment (vehicles, trains, ships, etc.)
- ⑦ Traffic signal equipment
- ⑧ Disaster prevention / crime prevention equipment
- ⑨ Data-processing equipment
- ⑩ Application of similar complexity and/or reliability requirements to the applications listed above

3 Product specifications in this catalog are as of December 2018. They are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. If there are any questions, please contact our sales representatives or product engineers.

4 Please read rating and  $\Delta$ CAUTION (for storage, operating, rating, soldering, mounting and handling) in this catalog to prevent smoking and/or burning, etc.

5 This catalog has only typical specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

6 Please note that unless otherwise specified, we shall assume no responsibility whatsoever for any conflict or dispute that may occur in connection with the effect of our and/or a third party's intellectual property rights and other related rights in consideration of your use of our products and/or information described or contained in our catalogs. In this connection, no representation shall be made to the effect that any third parties are authorized to use the rights mentioned above under licenses without our consent.

7 No ozone depleting substances (ODS) under the Montreal Protocol are used in our manufacturing process.

Murata Manufacturing Co., Ltd.

[www.murata.com](http://www.murata.com)

**muRata**  
INNOVATOR IN ELECTRONICS

Headquarter Switzerland:  
Angst+Pfister Sensors and Power AG

Thurgauerstrasse 66  
CH-8050 Zurich  
Phone +41 44 877 35 00  
sensorsandpower@angst-pfister.com

Office Germany:  
Angst+Pfister Sensors and Power  
Deutschland GmbH  
Edisonstraße 16  
D-85716 Unterschleißheim  
Phone +49 89 374 288 87 0  
sensorsandpower.de@angst-pfister.com



## We are here for you. Addresses and Contacts.

### Sales Germany & Austria

Geometrical sensors  
Other products

Kurt Stritzelberger  
Phone +49 89 374 288 87 22  
kurt.stritzelberger@angst-pfister.com

Pressure sensors  
Other products

Gerhard Vetter  
Phone +49 89 374 288 87 26  
gerhard.vetter@angst-pfister.com

Gas sensors and modules

Peter Felder  
Phone +41 44 877 35 05  
peter.felder@angst-pfister.com

### Sales Switzerland & Liechtenstein

Postcode 3000 – 9999

Basil Frei  
Phone +41 44 877 35 18  
basil.frei@angst-pfister.com

Postcode 1000 – 2999

Christian Mohrenstecher  
Phone +41 76 444 57 93  
christian.mohrenstecher@angst-pfister.com

### Sales International Key Accounts

Peter Felder  
Phone +41 44 877 35 05  
peter.felder@angst-pfister.com

### Sales Other Countries / Product Management

Pressure Sensors  
Load Cells

Philipp Kistler  
Phone +41 44 877 35 03  
philipp.kistler@angst-pfister.com

Gas sensors  
Gas sensor modules

Dr. Thomas Clausen  
Phone +49 89 374 288 87 24  
thomas.clausen@angst-pfister.com

Flow / Level / Medical products

Dr. Adriano Pittarelli  
Phone +49 89 374 288 87 67  
adriano.pittarelli@angst-pfister.com

Power supplies

Sebastiano Leggio  
Phone +41 44 877 35 06  
sebastiano.leggio@angst-pfister.com

Linear position sensors  
Angle sensors

Eric Letsch  
Phone +41 44 877 35 14  
eric.letsch@angst-pfister.com

Accelerometers  
Sensor elements

Christoph Kleye  
Phone +49 89 374 288 87 61  
christoph.kleye@angst-pfister.com

Drive technology  
CH Postcode 5000 – 9999 / DE

Roman Homa  
Phone +41 76 444 00 86  
roman.homa@angst-pfister.com

Drive technology  
CH Postcode 1000 – 4999 / AT / IT / FR

Christian Mohrenstecher  
Phone +41 76 444 57 93  
christian.mohrenstecher@angst-pfister.com

Harald Thomas  
Phone +49 89 374 288 87 23  
harald.thomas@angst-pfister.com