

PEWA2701 Digital Output Pressure Sensor



Features

- Gauge, absolute, sealed gauge
- Isolated construction, enable to measure various liquid
- Standard sensor dimension, wide range of applications

Application

- Industrial process control
- Gas, liquid pressure measurement
- Pressure checking meter
- Liquid pressure system and switch
- Cooling equipment and air conditioning system
- Aviation and navigation inspection

Introduction

PEWA2701 Digital Output Pressure Sensor is the OEM piezoresistive pressure sensor with 316L stainless steel corrugated diaphragm and isolated oil-filling construction. The sensing package utilizes silicone oil to transfer pressure from the 316L stainless steel diaphragm to the sensing die. The pressure is transformed to analog electric signal. By customized integrated circuit for temperature compensation and non-linearity correction, it outputs pressure data and temperature data conforming to I²C interface protocol or SPI interface protocol. With digital normalized output and low power consumption, it is convenient to connect to various devices, and has strong applicability. It is widely used for various liquid pressure measurement which is compatible with stainless steel and Viton.

Specifications

- Range: 0bar~0.07bar/0.2bar/0.35bar/0.7bar/1bar/2bar/3.5bar/5bar/7bar/10bar/16bar/20bar/35bar/70bar/100bar/200bar/350bar/700bar/1000bar
- Pressure Type: Gauge/ Absolute/Sealed Gauge
- Overpressure: 1.5FS or 1100bar (min. value is valid)
- Accuracy: $\pm 0.25\%$ FS (typ.); $\pm 0.5\%$ FS (max.)
- Output Digital Value: 1638 (zero)~14746 (span)
- Output Digits: 14 digits (max. 16383)
- Power Supply: 3.3 ± 0.1 V DC(default); 5 ± 0.1 V DC
- Power Consumption: 5uA (standby mode) @25 °C
- Long Term Stability: $\pm 0.2\%$ FS/year
- Working Temperature: -20 °C ~80 °C
- Storage Temperature: -40 °C ~125 °C
- Compensation temperature: -10 °C ~50 °C
- Shock: 10g, 20Hz~2000Hz
- Impact: 100g, 11ms


Note

Accuracy is $\pm 1\%$ when pressure is ≤ 0.35 bar, Accuracy is $\pm 0.5\%$ when pressure is ≥ 70 bar.


Sensor pressure output is 14-digit, the max. output digital value is 16383, but in order to leave a certain overpressure value, the upper and lower limits of the digital quantity are left 10% each, the zero and full values are 1638 and 14746.

| V2.1 01/2021

Outline Construction (Unit: mm)



Electrical Connection



Wire number (red: 1)	Electrical connection (I ² C)	Electrical connection (SPI)
1	V-	V-
2	V+	V+
3	SCL	SCLK
4	SDA	MISO
5	NULL	SS

Order Guide

PEWA2701		Digital Output Pressure Transducer			
	Range	Range: 0bar~0.07bar/0.2bar/0.35bar/0.7bar/1bar/2bar/3.5bar/5bar/7bar/10bar/16bar/20bar/35bar/70bar/100bar/200bar/350bar/700bar/1000bar			
	[0~X]bar	X: actual measured range			
		Code	Power Supply		
		3	(3.3±0.1)V DC (default)		
		5	(5±0.1)V DC		
		Code	Communication interface		
		C	I ² C		
		D	SPI		
		Code	Pressure Type		
		G	Gauge (Range≤35bar)		
		A	Absolute (Range≥0.7bar)		
		S	Sealed Gauge (Range≥35bar)		
PEWA2701	[0~X]bar	3	C	G	the whole spec.

Notes

1. Please pay attention that the measured media shall be compatible with contacted parts.
2. The sensor has temperature output which is a reference value. The reference precision is ± 1.5 °C (@ constant temperature condition) , If the sensor range≥70bar, no temperature output.
3. For special requirements, please contact us and make note in purchase order.

|v2.1 01/2021

We are here for you. Addresses and Contacts.

Headquarter Switzerland:

Angst+Pfister Sensors and Power AG
Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:

Angst+Pfister Sensors and Power Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 00
sensorsandpower.de@angst-pfister.com

Scan here and get an overview of personal contacts!



sensorsandpower.angst-pfister.com
