Related Devices | Buy Online | Spice Models | Contact Sales | Learn More

DATASHEET

# UF3SC120016K4S




| Part Number | Package | Marking |
|---|---|---|
| UF3SC120016K4S | TO-247-4L | UF3SC120016K4S |

## 1200V-16mΩ SiC FET

Rev. B, December 2019

## Description

This SiC FET device is based on a unique 'cascode' circuit configuration, in which a normally-on SiC JFET is co-packaged with a Si MOSFET to produce a normally-off SiC FET device. The device's standard gate-drive characteristics allows for a true "drop-in replacement" to Si IGBTs, Si FETs, SiC MOSFETs or Si superjunction devices. Available in the TO-247-4L package, this device exhibits ultra-low gate charge and exceptional reverse recovery characteristics, making it ideal for switching inductive loads , and any application requiring standard gate drive.

## Features

- Typical on-resistance $R_{DS(on),typ}$ of 16mΩ
- Maximum operating temperature of 175°C
- Excellent reverse recovery
- Low gate charge
- Low intrinsic capacitance
- ESD protected, HBM class 2
- TO-247-4L package for faster switching, clean gate waveforms

## Typical applications

- EV charging
- PV inverters
- Switch mode power supplies
- Power factor correction modules
- Motor drives
- Induction heating



Experts on Design-In
Angst+Pfister Sensors and Power

UnitedSiC
Related Devices Buy Online Spice Models Contact Sales Learn More

## Maximum Ratings

| Parameter | Symbol | Test Conditions | Value | Units |
|---|---|---|---|---|
| Drain-source voltage | $V_{DS}$ | | 1200 | V |
| Gate-source voltage | $V_{GS}$ | DC | -20 to +20 | V |
| Continuous drain current [1] | $I_D$ | $T_C$ = 25°C | 107 | A |
| | | $T_C$ = 100°C | 77 | A |
| Pulsed drain current [2] | $I_{DM}$ | $T_C$ = 25°C | 350 | A |
| Single pulsed avalanche energy [3] | $E_{AS}$ | L = 15mH, $I_{AS}$ =6.6A | 327 | mJ |
| Power dissipation | $P_{tot}$ | $T_C$ = 25°C | 517 | W |
| Maximum junction temperature | $T_{J,max}$ | | 175 | °C |
| Operating and storage temperature | $T_J$, $T_{STG}$ | | -55 to 175 | °C |
| Max. lead temperature for soldering, 1/8" from case for 5 seconds | $T_L$ | | 250 | °C |

1. Limited by $T_{J,max}$
2. Pulse width $t_p$ limited by $T_{J,max}$
3. Starting $T_J$ = 25°C

## Thermal Characteristics

| Parameter | Symbol | Test Conditions | Value | | | Units |
|---|---|---|---|---|---|---|
| | | | Min | Typ | Max | |
| Thermal resistance, junction-to-case | $R_{\theta JC}$ | | | 0.22 | 0.29 | °C/W |



Experts on Design-In
Angst+Pfister Sensors and Power

UnitedSiC
Related Devices | Buy Online | Spice Models | Contact Sales | Learn More

## Electrical Characteristics ($T_J$ = +25°C unless otherwise specified)

### Typical Performance - Static

| Parameter | Symbol | Test Conditions | Value | | | Units |
|---|---|---|---|---|---|---|
| | | | Min | Typ | Max | |
| Drain-source breakdown voltage | $BV_{DS}$ | $V_{GS}$=0V, $I_D$=1mA | 1200 | | | V |
| Total drain leakage current | $I_{DSS}$ | $V_{DS}$=1200V, $V_{GS}$=0V, $T_J$=25°C | | 1.2 | 300 | µA |
| | | $V_{DS}$=1200V, $V_{GS}$=0V, $T_J$=175°C | | 3.7 | | |
| Total gate leakage current | $I_{GSS}$ | $V_{DS}$=0V, $T_J$=25°C, $V_{GS}$=-20V / +20V | | 4.5 | ± 20 | µA |
| Drain-source on-resistance | $R_{DS(on)}$ | $V_{GS}$=12V, $I_D$=50A, $T_J$=25°C | | 16 | 21 | mΩ |
| | | $V_{GS}$=12V, $I_D$=50A, $T_J$=125°C | | 25 | | |
| | | $V_{GS}$=12V, $I_D$=50A, $T_J$=175°C | | 33 | | |
| Gate threshold voltage | $V_{G(th)}$ | $V_{DS}$=5V, $I_D$=10mA | 4 | 4.7 | 6 | V |
| Gate resistance | $R_G$ | f=1MHz, open drain | | 0.8 | 1.5 | Ω |

### Typical Performance - Reverse Diode

| Parameter | Symbol | Test Conditions | Value | | | Units |
|---|---|---|---|---|---|---|
| | | | Min | Typ | Max | |
| Diode continuous forward current [1] | $I_S$ | $T_C$=25°C | | | 107 | A |
| Diode pulse current [2] | $I_{S,pulse}$ | $T_C$=25°C | | | 350 | A |
| Forward voltage | $V_{FSD}$ | $V_{GS}$=0V, $I_F$=50A, $T_J$=25°C | | 1.47 | 2 | V |
| | | $V_{GS}$=0V, $I_F$=50A, $T_J$=175°C | | 1.95 | | |
| Reverse recovery charge | $Q_{rr}$ | $V_R$=800V, $I_F$=80A, $V_{GS}$=-5V, $R_{G_EXT}$=5Ω di/dt=1750A/µs, $T_J$=25°C | | 605 | | nC |
| Reverse recovery time | $t_{rr}$ | | | 66 | | ns |
| Reverse recovery charge | $Q_{rr}$ | $V_R$=800V, $I_F$=80A, $V_{GS}$=-5V, $R_{G_EXT}$=5Ω di/dt=1750A/µs, $T_J$=150°C | | 621 | | nC |
| Reverse recovery time | $t_{rr}$ | | | 72 | | ns |



Experts on Design-In
Angst+Pfister Sensors and Power

Related Devices Buy Online Spice Models Contact Sales Learn More

## Typical Performance - Dynamic

| Parameter | Symbol | Test Conditions | Value | | | Units |
|---|---|---|---|---|---|---|
| | | | Min | Typ | Max | |
| Input capacitance | $C_{iss}$ | $V_{DS}$=800V, $V_{GS}$=0V f=100kHz | | 7824 | | pF |
| Output capacitance | $C_{oss}$ | | | 216 | | |
| Reverse transfer capacitance | $C_{rss}$ | | | 3.1 | | |
| Effective output capacitance, energy related | $C_{oss(er)}$ | $V_{DS}$=0V to 800V, $V_{GS}$=0V | | 243 | | pF |
| Effective output capacitance, time related | $C_{oss(tr)}$ | $V_{DS}$=0V to 800V, $V_{GS}$=0V | | 540 | | pF |
| $C_{OSS}$ stored energy | $E_{oss}$ | $V_{DS}$=800V, $V_{GS}$=0V | | 78 | | µJ |
| Total gate charge | $Q_G$ | $V_{DS}$=800V, $I_D$=80A, $V_{GS}$ = -5V to 15V | | 218 | | nC |
| Gate-drain charge | $Q_{GD}$ | | | 24 | | |
| Gate-source charge | $Q_{GS}$ | | | 96 | | |
| Turn-on delay time | $t_{d(on)}$ | $V_{DS}$=800V, $I_D$=80A, Gate Driver =-5V to +15V, Turn-on $R_{G,EXT}$=1.5Ω, Turn-off $R_{G,EXT}$=5Ω Inductive Load, FWD: same device with $V_{GS}$ = -5V, $R_G$ = 5Ω, $T_J$=25°C | | 33 | | ns |
| Rise time | $t_r$ | | | 59 | | |
| Turn-off delay time | $t_{d(off)}$ | | | 73 | | |
| Fall time | $t_f$ | | | 12 | | |
| Turn-on energy | $E_{ON}$ | | | 2552 | | µJ |
| Turn-off energy | $E_{OFF}$ | | | 150 | | |
| Total switching energy | $E_{TOTAL}$ | | | 2702 | | |
| Turn-on delay time | $t_{d(on)}$ | $V_{DS}$=800V, $I_D$=80A, Gate Driver =-5V to +15V, Turn-on $R_{G,EXT}$=1.5Ω, Turn-off $R_{G,EXT}$=5Ω Inductive Load, FWD: same device with $V_{GS}$ = -5V, $R_G$ = 5Ω, $T_J$=150°C | | 33 | | ns |
| Rise time | $t_r$ | | | 63 | | |
| Turn-off delay time | $t_{d(off)}$ | | | 79 | | |
| Fall time | $t_f$ | | | 12 | | |
| Turn-on energy | $E_{ON}$ | | | 2820 | | µJ |
| Turn-off energy | $E_{OFF}$ | | | 154 | | |
| Total switching energy | $E_{TOTAL}$ | | | 2974 | | |



Experts on Design-In
Angst+Pfister Sensors and Power

UnitedSiC
Related Devices Buy Online Spice Models Contact Sales Learn More

## Typical Performance - Dynamic (continued)

| Parameter | Symbol | Test Conditions | Value | | | Units |
|---|---|---|---|---|---|---|
| | | | Min | Typ | Max | |
| Turn-on delay time | $t_{d(on)}$ | $V_{DS}$=800V, $I_D$=80A, Gate Driver =-5V to +15V, Turn-on $R_{G,EXT}$=1.5Ω, Turn-off $R_{G,EXT}$=5Ω Inductive Load, FWD: UJ3D1250K, $T_J$=25°C | | 33 | | ns |
| Rise time | $t_r$ | | | 58 | | |
| Turn-off delay time | $t_{d(off)}$ | | | 73 | | |
| Fall time | $t_f$ | | | 11 | | |
| Turn-on energy | $E_{ON}$ | | | 1815 | | µJ |
| Turn-off energy | $E_{OFF}$ | | | 140 | | |
| Total switching energy | $E_{TOTAL}$ | | | 1955 | | |
| Turn-on delay time | $t_{d(on)}$ | $V_{DS}$=800V, $I_D$=80A, Gate Driver =-5V to +15V, Turn-on $R_{G,EXT}$=1.5Ω, Turn-off $R_{G,EXT}$=5Ω Inductive Load, FWD: UJ3D1250K, $T_J$=150°C | | 33 | | ns |
| Rise time | $t_r$ | | | 64 | | |
| Turn-off delay time | $t_{d(off)}$ | | | 78 | | |
| Fall time | $t_f$ | | | 12 | | |
| Turn-on energy | $E_{ON}$ | | | 1947 | | µJ |
| Turn-off energy | $E_{OFF}$ | | | 158 | | |
| Total switching energy | $E_{TOTAL}$ | | | 2105 | | |



Experts on Design-In
Angst+Pfister Sensors and Power

Related Devices Buy Online Spice Models Contact Sales Learn More

## Typical Performance Diagrams




Figure 1. Typical output characteristics at $T_J$ = - 55°C, tp < 250µs




Figure 2. Typical output characteristics at $T_J$ = 25°C, tp < 250µs




Figure 3. Typical output characteristics at $T_J$ = 175°C, tp < 250µs




Figure 4. Normalized on-resistance vs. temperature at $V_{GS}$ = 12V and $I_D$ = 50A



Experts on Design-In
Angst+Pfister Sensors and Power

UnitedSiC
Related Devices Buy Online Spice Models Contact Sales Learn More




Figure 5. Typical drain-source on-resistances at $V_{GS}$ = 12V




Figure 6. Typical transfer characteristics at $V_{DS}$ = 5V




Figure 7. Threshold voltage vs. junction temperature at $V_{DS}$ = 5V and $I_D$ = 10mA




Figure 8. Typical gate charge at $V_{DS}$ = 800V and $I_D$ = 80A



Experts on Design-In
Angst+Pfister Sensors and Power

UnitedSiC
Related Devices Buy Online Spice Models Contact Sales Learn More




Figure 9. 3rd quadrant characteristics at $T_J$ = -55°C




Figure 10. 3rd quadrant characteristics at $T_J$ = 25°C




Figure 11. 3rd quadrant characteristics at $T_J$ = 175°C




Figure 12. Typical stored energy in $C_{OSS}$ at $V_{GS}$ = 0V



Experts on Design-In
Angst+Pfister Sensors and Power

Related Devices Buy Online Spice Models Contact Sales Learn More




Figure 13. Typical capacitances at f = 100kHz and $V_{GS}$ = 0V




Figure 14. DC drain current derating




Figure 15. Total power dissipation




Figure 16. Maximum transient thermal impedance



Experts on Design-In
Angst+Pfister Sensors and Power

UnitedSiC
Related Devices Buy Online Spice Models Contact Sales Learn More




Figure 17. Safe operation area at $T_C$ = 25°C, D = 0, Parameter $t_p$




Figure 18. Clamped inductive switching energy vs. drain current at $T_J$ = 25°C




Figure 19. Clamped inductive switching turn-on energy vs. $R_{G,EXT_ON}$




Figure 20. Clamped inductive switching turn-off energy vs. $R_{G,EXT_OFF}$



Experts on Design-In
Angst+Pfister Sensors and Power

UnitedSiC
Related Devices Buy Online Spice Models Contact Sales Learn More




Figure 21. Clamped inductive switching energy vs. junction temperature at $V_{DS}$ = 800V and $I_D$ = 80A




Figure 22. Reverse recovery charge Qrr vs. junction temperature




Figure 23. Clamped inductive switching energy vs. drain current at $T_J$ = 25°C




Figure 24. Clamped inductive switching energy vs. junction temperature at $V_{DS}$ = 800V and $I_D$ = 80A



Experts on Design-In
Angst+Pfister Sensors and Power

Related Devices Buy Online Spice Models Contact Sales Learn More

## Applications Information

SiC FETs are enhancement-mode power switches formed by a high-voltage SiC depletion-mode JFET and a low-voltage silicon MOSFET connected in series. The silicon MOSFET serves as the control unit while the SiC JFET provides high voltage blocking in the off state. This combination of devices in a single package provides compatibility with standard gate drivers and offers superior performance in terms of low on-resistance ($R_{DS(on)}$), output capacitance ($C_{oss}$), gate charge ($Q_G$), and reverse recovery charge (Qrr) leading to low conduction and switching losses. The SiC FETs also provide excellent reverse conduction capability eliminating the need for an external anti-parallel diode.

Like other high performance power switches, proper PCB layout design to minimize circuit parasitics is strongly recommended due to the high dv/dt and di/dt rates. An external gate resistor is recommended when the FET is working in the diode mode in order to achieve the optimum reverse recovery performance. For more information on SiC FET operation, see www.unitedsic.com.

## Disclaimer

UnitedSiC reserves the right to change or modify any of the products and their inherent physical and technical specifications without prior notice. UnitedSiC assumes no responsibility or liability for any errors or inaccuracies within.

Information on all products and contained herein is intended for description only. No license, express or implied, to any intellectual property rights is granted within this document.

UnitedSiC assumes no liability whatsoever relating to the choice, selection or use of the UnitedSiC products and services described herein.



Experts on Design-In
Angst+Pfister Sensors and Power

Angst+Pfister
Sensors and Power

# We are here for you. Addresses and Contacts.


Headquarter Switzerland:

Angst+Pfister Sensors and Power AG
Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:

Angst+Pfister Sensors and Power Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 00
sensorsandpower.de@angst-pfister.com


Scan here and get an overview of personal contacts!

sensorsandpower.angst-pfister.com