

Oxygen (O₂) - Industrial Sensor / Type P-41AGW

Sensor designed to detect trace amounts of oxygen, analog sensor output signal, temperature compensated signal, thread for easy gas adaptation, resistant to acid gases, hydrocarbons and hydrogen.

All characteristics are based on conditions at 25°C, 50% RH and 1013 hPa.



Measurement Range:	1 to 5 Vol.% O ₂
Overload:	> 5 Vol.%O ₂
Sensor Lifetime:	1 year, depending on ambient humidity and O ₂ concentration
Mechanical Mating Connector:	fits for M16x1 DIN 13 or 5/8-24 UNEF
Electrical Connector:	3-Pin Molex® (analog sensor output signal)
Initial Output Signal Range:	0.45 - 0.7 mV @ 1 Vol.%O ₂
Response Times (in operation):	< 180 s from 10,000 ppm down to 1,000 ppm < 10 min from 1,000 ppm down to 250 ppm < 5 h from 10 ppm down to <1 ppm
Linearity Error:	± 2 % of signal
Pressure Dependency:	partial pressure
Operating Temperature:	0 to 50 °C
Temperature Compensation:	NTC on sensor PCB (sensor output signal is already temperature compensated)
Weight:	approximately 47 g
Material in Contact with Media:	PVDF, PTFE, stainless steel

STORAGE CONDITIONS IN UNOPENED ORIGINAL PACKAGE

Packaging:	sealed nitrogen flushed coated plastic bag
Temperature Range:	recommended: 5 to 25 °C maximum: 0 to 45 °C
Ambient Pressure:	600 to 1750 hPa
Humidity:	up to 100 % RH, non-condensing
Shelf Life:	< 3 months recommended

We are here for you. Addresses and Contacts.

Headquarter Switzerland:

Angst+Pfister Sensors and Power AG
Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:

Angst+Pfister Sensors and Power Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 00
sensorsandpower.de@angst-pfister.com

Scan here and get an overview of personal contacts!



sensorsandpower.angst-pfister.com
