




		Conception	Type de capteur	Nombres d'axes	Vitesse angulaire [$\pm$ °/s]	Accélération [$\pm$ g]	Plage de mesure	Sensibilité	Bruit de fond
	SCH16T-K01	IC	6-DoF Sensor	6	300	1.5 / 8 / 26	300°/s	100 / 1600 LSB/(°/sec)	0,0006°/s rms
	SCH16T-K01-PCB (avail. in June)	Evalboard	6-DoF Evalboard	6	300	1.5 / 8 / 26	300°/s	100 / 1600 LSB/(°/sec)	0,0006°/s rms
	SCHA63T-K01	IC	6-DoF Sensor		125		125°/s	160 LSB/(°/sec)	0,0011°/s rms
	SCHA63T-K03	IC	6-DoF Sensor	6	300	6	300°/s	80 LSB/(°/sec)	0,0014°/s rms
	SCHA63T-K06	IC	6-DoF Sensor	6	300	6, 14.6	300°/s	80 LSB/(°/sec)	0.0015
	APUM-SCHA63T	Evalboard	Open IMU Evaluation board	6	300	6 / 14.6	300°/s	80 LSB/(°/sec)	0,0015°/s rms
	SCHA63T-K03-PCB	Platine	6-DoF Evalboard		300	6	300°/s	80 LSB/(°/sec)	0,0014°/s rms
	AP-EVAL-SCHA600-PCB (Last time buy 29. Feb 2024)	Evalboard							

		Conception	Type de capteur	Nombres d'axes	Vitesse angulaire [$\pm$ °/s]	Accélération [$\pm$ g]	Plage de mesure	Sensibilité	Bruit de fond
	SCC433T-K03	IC	5-DoF Sensor	4	300	6,8	300 °/s	80 LSB/(°/sec)	0,0009 °/s rms
	SCR410T-K03	IC	Gyro	1	300	6,8	300 °/s	80 LSB/(°/sec)	0,0009 °/s rms
	AP-EVAL-AGPCK40	Evalboard	Open IMU Evaluation board		125		125 °/s	160 LSB/(°/sec)	0,0011 °/s rms
	AP-EVAL-AGPCK41	Evalboard	Open IMU Evaluation board		300		300 °/s	80 LSB/(°/sec)	0,0014 °/s rms
	AP-LOGGER-Breakout (Last time Buy 31.March 2024)	Evalboard							
	AP-Logger (Last time buy 31.March 2024)	Evalboard	AP-LOGGER						
	DMU41	Plug & Play Module	IMU	6	490	10	490 °/s, 10 g		0.05 °/s rms, 0.9 mg
	DMU11	Platine	IMU	6	300	10	300 °/s, 10 g		0.1 °/s rms

		Conception	Type de capteur	Nombres d'axes	Vitesse angulaire [$\pm^\circ/\text{s}$]	Accélération [$\pm g$]	Plage de mesure	Sensibilité	Bruit de fond
	DMU11-21-0500	Evalboard	IMU evaluation kit	6	300	10	300 $^\circ/\text{s}$, 10 g		0.1 $^\circ/\text{s}$ rms
	CRM100	IC	Gyro	1	75, 150, 300, 900		75, 150, 300, 900 $^\circ/\text{s}$	12, 6, 3, 1 mV/ $^\circ/\text{s}$	0.18 $^\circ/\text{s}$ rms
	CRM200	IC	Gyro	1	75, 150, 300, 900		75, 150, 300, 900 $^\circ/\text{s}$	12, 6, 3, 1 mV/ $^\circ/\text{s}$	0.18 $^\circ/\text{s}$ rms
	CRM202	IC	Gyro	1	900, 2700		900 to 2700 $^\circ/\text{s}$	1 mV/ $^\circ/\text{s}$	0.18 $^\circ/\text{s}$ rms
	CRM102	IC	Gyro	1	900, 2700		900 to 2700 $^\circ/\text{s}$	1 mV/ $^\circ/\text{s}$	0.18 $^\circ/\text{s}$ rms
	CRS39A	Platine	Gyro	1	25		27 $^\circ/\text{s}$	80 mV/ $^\circ/\text{s}$	0.03 $^\circ/\text{s}$ rms
	CMS300 Orion	IC	Combi sensor	3	150, 300	2.5, 10	150, 300 $^\circ/\text{s}$, 2.5 g, 10 g	204.8 lsb/ $^\circ/\text{s}$ ($\pm 150^\circ/\text{s}$), 102.4 lsb/ $^\circ/\text{s}$ ($\pm 300^\circ/\text{s}$)	0.06 $^\circ/\text{s}$ rms
	CMS390 ORION	IC	Combi sensor	3	150, 300	2.5, 10	150, 300 $^\circ/\text{s}$, 2.5 g, 10 g	204.8 lsb/ $^\circ/\text{s}$ ($\pm 150^\circ/\text{s}$), 102.4 lsb/ $^\circ/\text{s}$ ($\pm 300^\circ/\text{s}$)	0.06 $^\circ/\text{s}$ rms

		Conception	Type de capteur	Nombres d'axes	Vitesse angulaire [$\pm$ °/s]	Accélération [$\pm$ g]	Plage de mesure	Sensibilité	Bruit de fond
	CMS300-02-0302	Platine	Combi sensor evalboard	3	150, 300	2.5, 10	150, 300 °/s, 2.5 g, 10 g		0.06 °/s rms
	CMS390-02-0302	Platine	Combi sensor evalboard	3	150, 300	2.5, 10	150, 300 °/s, 2.5 g, 10 g		0.06 °/s rms
	CRS43	Plug & Play Module	Gyro	1	100, 200		100, 200 °/s	20, 10 mV/°/s	0.18 °/s rms
	400046-0300 CRM 3-Axis EVB	Evalboard	Gyro evalboard	3	75, 150, 300, 900		75, 150, 300, 900 °/s	12, 6, 3, 1 mV/°/s	0.18 °/s rms
	400046-0100 CRM100 EVB	Evalboard	Gyro evalboard	1	75, 150, 300, 900		75, 150, 300, 900 °/s	12, 6, 3, 1 mV/°/s	0.18 °/s rms
	400046-0200 CRM200 EVB	Evalboard	Gyro evalboard	1	75, 150, 300, 900		75, 150, 300, 900 °/s	12, 6, 3, 1 mV/°/s	0.18 °/s rms
	SCC1300-D04	IC	Combi Sensor	4	300	6	300 °/s, 6g	18 LSB/(°/sec)	0,14 °/s rms
	SCR1100-D04	IC	Gyro	1	300		300 °/s	18 LSB/(°/sec)	0,14 °/s rms

		Conception	Type de capteur	Nombres d'axes	Vitesse angulaire [$\pm$ °/s]	Accélération [$\pm$ g]	Plage de mesure	Sensibilité	Bruit de fond
	SCC2230-D08	IC	Combi Sensor	4	125	6	125°/s, 6g	50 LSB/(°/sec)	0,08 °/s rms
	SCC2230-E02	IC	Combi Sensor	4	125	2	125°/s, 2g	50 LSB/(°/sec)	0,08 °/s rms
	SCR2100-D08	IC	Gyro	1	125		125°/s	50 LSB/(°/sec)	0,05 °/s rms
	SCR2100-D15	IC	Gyro	1	300		300°/s	50 LSB/(°/sec)	0,12 °/s rms
	SCR2200-D13	IC	Gyro	1	125		125°/s	50 LSB/(°/sec)	0,12 °/s rms
	SCR2200-D15	IC	Gyro	1	300		300°/s	50 LSB/(°/sec)	0,12 °/s rms

We are here for you. Addresses and Contacts.

Headquarter Switzerland:

Angst+Pfister Sensors and Power AG
Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:

Angst+Pfister Sensors and Power Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 00
sensorsandpower.de@angst-pfister.com

Scan here and get an overview of personal contacts!



sensorsandpower.angst-pfister.com