



















		BUS	Inputs	Mbps	Nodes	BUS ESD	Principales caractéristiques	Forfaits disponibles
	**IL41050TT**	CAN	digital	1	110	4kV	Low Cost, 2.5kV Isolation	0.3 SOIC16"
	**IL3685**	RS-485	digital	40	50	15kV	PROFIBUS	0.15 SOIC16, 0.3" SOIC16, QSOP16"
	**IL3585**	RS-485	digital	40	50	15kV	Very High Speed	0.15 SOIC16, 0.3" SOIC16"
	**IL3685V**	RS-485	digital	40	50	15kV	PROFIBUS, 6kV Isolation	0.15 SOIC16, 0.3" SOIC16, QSOP16"
	**IL3585V**	RS-485	digital	40	50	15kV	Very High Speed, 6kV Isolation	0.15 SOIC16, 0.3" SOIC16"
	**IL4822 / IL4622 / IL4685**	RS-485	digital	40	160	16.5kV	Very High Speed	0.3" SOIC16
	**IL3685P**	RS-485	digital	40	160	16.5kV	Very High Speed	0.3" SOIC16, QSOP16
	**IL41050TTV**	CAN	digital	1	110	4kV	Low Cost, 5kV Isolation	0.3 SOIC16"

		BUS	Inputs	Mbps	Nodes	BUS ESD	Principales caractéristiques	Forfaits disponibles
	**IL41050TA**	CAN	digital	1	110	4kV	125°C, Silent Mode	0.15 SOIC16, 0.3" SOIC16, QSOP16"
	**IL41050TFD**	CAN-FD	digital	5	110	4kV	CAN-FD	0.15 SOIC16, 0.3" SOIC16, QSOP16"
	**IL3122**	RS-422	passive	5	32	15kV	Low Cost	0.15 SOIC16, 0.3" SOIC16"
	**IL3185**	RS-485	passive	5	32	15kV	Low Cost	0.15 SOIC16, 0.3" SOIC16"
	**IL3222**	RS-422	passive	5	256	15kV	Fractional Load	0.15 SOIC16, 0.3" SOIC16"
	**IL3285**	RS-485	passive	5	256	15kV	Fractional Load	0.15 SOIC16, 0.3" SOIC16"
	**IL3422**	RS-422	passive	20	32	15kV	High Speed	0.15 SOIC16, 0.3" SOIC16"
	**IL3485**	RS-485	passive	20	32	15kV	High Speed	0.15 SOIC16, 0.3" SOIC16"

		BUS	Inputs	Mbps	Nodes	BUS ESD	Principales caractéristiques	Forfaits disponibles
	**IL2985**	RS-485	digital	4	32	7.5kV	Low Power	0.3 SOIC16"
	**IL3022**	RS-422	digital	4	32	7.5kV	Low Cost	0.3 SOIC16"
	**IL3085**	RS-485	digital	4	32	7.5kV	Low Cost	0.15 SOIC16, 0.3" SOIC16, QSOP16"
	**IL3522**	RS-422	digital	40	50	15kV	Very High Speed	0.3 SOIC16"
	**IL3522V**	RS-422	digital	40	50	15kV	Very High Speed, 6kV Isolation	0.3 SOIC16"
	**IL76xxV Serie**	RS-485, SPI	digital	40	50	5kV	High Speed Digital Isoaltion 110Mpbs, 6kV with DCDC converter 3.3V	SOIC16W
	**IL71xx-Serie**	RS-485, SPI	digital	40	50	5kV	High Speed Digital Isoaltion 110Mpbs, 6kV with DCDC converter 3.3V	SOIC16W

Angst+Pfister
Sensors and Power

We are here for you. Addresses and Contacts.

Headquarter Switzerland:

Angst+Pfister Sensors and Power AG
Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:

Angst+Pfister Sensors and Power Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 00
sensorsandpower.de@angst-pfister.com

Scan here and get an overview of personal contacts!

sensorsandpower.angst-pfister.com